

### **Cutting table MF 7240**

Cutting width (m) 4.20 - 5.40

Cutting frequency (stroke/min.) 1220

No. of chains 3

Fingers over entire width

### **Threshing system**

Drum width (mm) 1340

Drum diameter (mm) 600

Threshing drum speed (rev/min) 380 – 1210

Wrapping angle threshing concave degrees 120

Concave area (m<sup>2</sup>) 0.83

Independent setting front and back I

### **Separation system**

Total powered separation area (m<sup>2</sup>) 0.99

No. of straw walkers 5

No. of steps 4

Walker length (mm) 4256

Straw walker area (m<sup>2</sup>) 5

Total separation area (m<sup>2</sup>) 6.72

### **Cleaning system**

Fan type Radial

Fan speed (rev/min) 350 - 1050

Fan speed reduction kit (rev/min) 270 – 840

Returns material to drum I

Total sieve area (m<sup>2</sup>) 4.67

### **Straw Management**

Straw chopper I

52 knives I

Double serrated knives I

Single lever switch-over for straw chopper I

### **Grain tank**

Capacity (l) 5200

Unloading rate (l/sec) 85

Unloading type Turret unloading

Swivel angle of unloading auger degrees 100

Max. unloading height (m) 4.20

### **Engine**

Engine type make IVECO NEF

Cubic capacity (l) 6.7

Power (kW/ hp) 129/ 176

Fuel tank (l) 450

### **Drive**

Hydrostatic drive

Number of gears 3

### **Cab**

Mechanically suspended driver's seat

Heating

Air conditioning

Monitor

### **Weights and dimensions**

Height (transport position) (mm) 4000

Length with chopper (mm) 8700

Weight \* (kg) 10.300

### **Tyres**

Front (standard) 620/75R30

Rear (standard) 405/70-20

Transport width with tyres:

620/75R30 (mm) 3195