



88hp/65 kW

# MF 2168

Simple yet powerful machinery  
for rice, wheat and barley



FROM MASSEY FERGUSON

# Specifications

Full feed rubber track	<b>MF 2168</b>	
	●	
<b>Dimensions</b>		
In work status - Length (mm)	4800	5020
In work status - Width (mm)	2350	2350
In work status - Height (mm)	2900	2900
Total weight (kg)	2920	3020
Minimum ground clearance (mm)	310	
Average diesel consumption (kg/h m <sup>2</sup> )	≤ 30	
<b>Engine</b>		
Type	A498BZT88/24 - 4cyl water cooled	
Power rating hp (kW)	88hp (65kW)	
Rated rotor speed (rpm)	2400	

● Standard

<b>Cutting table</b>		<b>MF 2168</b>
Harvest width (m)	2.0m - 2.2m	
Horizontal cutter	Grade II	
Side vertical cutter	Grade II	
Cross Auger type	Screw auger, eccentric extensible link	
Reel type	Eccentric spring tooth	
Reel Diameter (mm)	900	
Reel plate No. (PC)	5	
<b>Threshing system</b>		
Main threshing drum	Transverse flow nail	
Secondary threshing drum	Transverse flow nail	
Main threshing drum (mm)	546 x 1285	
Secondary threshing drum (mm)	545 x 650	
Threshing drum No. (PC)	2	
Concave	Grid	
Cleaning system	Wind sieve	
Fan	Centrifugal	
Fan No.	1	
Fan Diameter (mm)	328	
Re-threshing drum	Impeller	
Discharge auger - diameter and Length (mm)	120 x 1400	
Returns	To drum	